

## TWO-DIMENSIONAL IMAGE PICKUP APPARATUS

### BACKGROUND OF THE INVENTION

#### Field of the Invention

5           This invention relates to a two-dimensional image pickup apparatus and, more particularly, it relates to a two-dimensional image pickup apparatus adapted to X-ray photography.

#### Related Background Art

10     ~~FIG. 1 of the accompanying drawings schematically illustrates a known image pickup apparatus adapted to X-ray photography and comprising a fluorescent member (e.g. scintillator) 1 for converting X-rays into rays of visible light, photoelectric converters 2a for converting visible light into electric signals, a substrate 2b carrying the photoelectric converter 2a thereon, a base member 7 supporting the substrate 2b thereon, circuit boards 5a, 5b for processing electric signals produced by photoelectric conversion, wires connected to the circuit boards and an apparatus cabinet 8 containing the above components.~~

25           The substrate 2b arranged under the photoelectric converters 2a (hereinafter referred to simply as substrate) is typically made of glass because it is required to be free from chemical reactions with the photoelectric converters of semiconductor, resist

the high temperature of the semiconductor forming process and maintain dimensional stability. The fluorescent member 1 is prepared by applying a fluorescent material of a metal compound to a resin plate. The gap separating the fluorescent member 1 and the photoelectric converters 2a has to be held to a sufficiently small value (typically less than tens of several micrometers) relative to the size of the pixels of the photoelectric converters 2a and, in most cases, the fluorescent member 1 and the substrate 2b are bonded together. Note that, in FIG. 1, photoelectric converter unit 102 refers to an assembly of a fluorescent member 1, a moisture-impermeable film 6 and other members arranged on the substrate 2b.

*insert A2.* When the photoelectric converters 2a are required to be moisture-resistant, the fluorescent member 1 and the photoelectric converters 2a may be wrapped and hermetically sealed by a moisture-impermeable and X-ray transmissive film 6.

Then, they are bonded and securely held to the base member 7 before contained in the apparatus cabinet 8 to complete the operation of assembling the image pickup apparatus for X-ray photography.

*insert A3.* Such image pickup apparatuses are conventionally used for X-ray photography as stationary apparatus. However, in recent years, there is an increasing demand for lightweight, compact and portable

A3  
cancel

image pickup apparatus adapted to rapid imaging operations for producing fine images.

insert  
A4

5 Additionally, image pickup apparatus having the above described configuration are required to safeguard the substrate 2b and other related components against impacts that can be applied thereto during transportation and the apparatus are also required to be safeguarded as a whole against deformations that can be caused by the external load (mainly the weight of  
10 the person to be photographed) of the apparatus during X-ray photographing operations. To meet these requirements, then the apparatus cabinet 8 has to be structurally very robust and this necessity of being robust has been obstructing the attempt to down-size  
15 and reduce the weight of the apparatus.

#### SUMMARY OF THE INVENTION

insert  
A5

20 In view of the above described circumstances, it is therefore the object of the present invention to provide an image pickup apparatus for X-ray photography structurally adapted to absorb external impacts and possible resultant deformations such as deflections of the cabinet so that the interior is protected against damage and remains intact if the cabinet is deformed by  
25 the external load.

insert  
A6

According to the invention, the above object of the invention is achieved by providing a

two-dimensional image pickup apparatus comprising an apparatus cabinet containing therein a substrate member and a photoelectric converter unit having a plurality of photoelectric converters formed on the substrate member, at least the photoelectric converter unit being arranged on a base member and the portion of the cabinet located opposite to its light receiving section is deformable.

Preferably, the portion of the cabinet located opposite to the light receiving section can restore the original position after deformation.

Preferably, the magnitude of deformation of the portion of the cabinet located opposite to the light receiving section is greater than that of the substrate member.

According to the invention, there is also provided an image pickup apparatus comprising a substrate, a photoelectric converter unit having a plurality of photoelectric converters and a cabinet containing the photoelectric converter unit, a shock absorbing means being arranged between the photoelectric converter unit and the cabinet.

For the purpose of the invention, the shock absorbing means may be containers.

For the purpose of the invention, the containers may contain gas in a sealed state.

A two-dimensional image pickup apparatus

A4  
concl

invent  
A7

invent  
A8

invent  
A9

invent  
A10

*APD*  
*anal*

according to the invention may further comprise a circuit board for processing electric signals from the photoelectric converters also contained in the apparatus cabinet and cooling liquid is contained in a sealed state at least in the containers held in direct contact with the electronic parts arranged on the circuit board.

#### BRIEF DESCRIPTION OF THE DRAWINGS

*Insert A11*

FIG. 1 is a schematic cross sectional view of a typical two-dimensional image pickup apparatus.

*Insert A12*

FIGS. 2, 3A, 4 and 5 are schematic cross sectional views of embodiments of two-dimensional image pickup apparatus according to the invention.

*Insert A13*

FIG. 3B is a schematic perspective view of the embodiment of two-dimensional image pickup apparatus of FIG. 3A.

#### DESCRIPTION OF THE PREFERRED EMBODIMENTS

Now, the present invention will be described in greater detail by referring to the accompanying drawings that illustrate preferred embodiments of the invention. However, the present invention is by no means limited to the embodiments as illustrated and described below, which may be modified appropriately in different ways without departing from the scope of the invention.

(First Embodiment)

*insert  
pg 9*  
FIG. 2 is a schematic cross sectional view of a first embodiment of the invention. In FIG. 2, the components same as or similar to those of the apparatus of FIG. 1 are denoted respectively by the same reference symbols.

In this embodiment, at least the top plate 81 constituting the cabinet is made of an easily deformable material. As a result, the top plate 81 deforms only within the space between the top plate 81 and the photoelectric converter unit 102 if a small impact is applied to it so that the impact will not be transmitted to the photoelectric converter unit 102 or, if transmitted, the effect of the impact can be significantly reduced.

Additionally, the base member 7 rigidly carrying the photoelectric converter unit 102 thereon shows a rigidity (resistance against deformation by force) greater than that of the top plate 81 so that, if a load 201 is applied to the top plate 81, the magnitude of deformation of the base member 7 due to the load is smaller than that of top plate 81 and hence the impact of the load is borne by the base member 7 to protect the photoelectric converter unit 102 against deformation and damage.

The top plate 81 is preferably made of a material that is highly impact-resistant and resilient

so that it may restore the original profile once the load or some other external force that has been applied to it is removed. Specific examples of materials that can be used for the top plate 81 include carbon- or  
5 Kevlar-reinforced resin, polyamide resin and polyimide resin. Above all, the use of carbon-fiber-reinforced resin is highly preferable in view of the X-ray transmittivity of the material.

(Second Embodiment)

10 *main AB* FIGS. 3A and 3B schematically illustrate a second embodiment of the invention, which will be specifically described below. There are shown a fluorescent member 1, two-dimensionally arranged photoelectric converters 2a, a substrate 2b typically  
15 made of glass and a moisture-impermeable film 6, of which the moisture-impermeable film 6, the fluorescent member 1 and the substrate 2b are bonded together.

Reference symbol 5a denotes a flexible circuit board for taking out signals from the photoelectric  
20 converters and reference symbol 5b denotes a circuit board for processing signals, which circuit boards are folded and arranged on the rear surface of the substrate 2b for the purpose of down-sizing. The above components are typically made of a glass plate or a  
25 semiconductor material and hence they are fragile and poorly resistant against impact.

The space between the components and the

apparatus cabinet 8 is filled with containers 9 containing air or other gases in the inside in a hermetically sealed state as shock absorbing means.

The containers 9 are made of an X-ray transmissive elastic material to define the positions of the photoelectric converters 2a relative to the apparatus cabinet 8 and absorb any load-induced impact through the compressive deformation of the internal gas in order to protect the substrate 2b and other fragile components against impact during transportation.

During an X-ray photographing operation, the image pickup apparatus 8 is subjected to the load of the object to be photographed and can become deflected or otherwise deformed. However, the containers 9 distribute the load and prevent the load from being intensively borne by part of the substrate 2b to get damaged.

Since the apparatus cabinet 8 itself is required to be transmissive of X-rays and lightweight as pointed out above, it is typically formed by combining a metal plate and CFRP (carbon-fiber-reinforced plastic) but the load bearing capacity of the apparatus cabinet 8 (that may be improved by increasing the thickness of the cabinet to baffle the effort of reducing its weight) does not particularly have to be taken into consideration because the containers 9 operate as reinforcement for



A17  
cancel

protecting the inner components as they are elastically deformed.

(Third Embodiment)

FIG. 4 schematically illustrates a third  
5 embodiment of the invention also comprising containers  
9, of which at least those held in direct contact with  
the electronic parts 5c arranged on the circuit board  
5b are made to contain cooling liquid 9a therein in a  
hermetically sealed state in order to cool them because  
10 many of the electronic parts 5c consume power and  
generate heat. As a result, the electronic parts are  
encouraged to emit heat so that malfunctions of the  
circuit due to heat can be avoided and the cabinet can  
be down-sized in an effective way.

15  
cancel  
A18

The containers 9 containing cooling liquid in a  
sealed state are preferably held in contact with the  
electronic parts 5c and, at the same time, with the  
apparatus cabinet 8. Those portions of the apparatus  
cabinet 8 that are held in contact with the related  
20 containers 9 is advantageously made of a thermally  
highly conductive material such as metal.  
Additionally, the apparatus cabinet 8 may be provided  
with heat-emitting fins (not shown), whose dimensions  
are, of course, confined within a permissible limit.

25 (Fourth Embodiment)

While the profile and the size of the  
containers 9 operating as shock absorbing means are not

particularly limited, FIG. 5 shows a single container 9 arranged at the side for receiving X-rays 101 to entirely or mostly cover the light receiving surface of the photoelectric converter unit 102.

5               With such an arrangement, the possible absorption, if any, of X-rays by the light receiving side container 9 along the direction of transmission can be minimized to improve the resolution of the transmitted X-rays.

10              The containers 9 may contain a gelled or deformable solid material in place of gas or liquid, although the transmittivity of electromagnetic waves having a desired wavelength has to be carefully taken into consideration at the light receiving side of the  
15     photoelectric converter unit.

*Insert  
A19*           As described above in detail, an image pickup apparatus adapted to X-ray photography according to the invention shows an improved shock-absorbing property and an enhanced load bearability to allow the apparatus  
20     to be further down-sized and become lightweight.

              As a result, it is now possible to realize a portable two-dimensional image pickup apparatus.

              As described above, the present invention provides a two-dimensional image pickup apparatus  
25     comprising a substrate, photoelectric converters formed on the substrate and an apparatus cabinet containing said substrate and said photoelectric converters, a

plurality of shock-absorbing members such as air bags  
being inserted into the gap between said substrate and  
said apparatus cabinet to prevent the inner wall  
surface of said apparatus cabinet and said substrate  
5 from contacting each other. With such an arrangement,  
if the cabinet and the top plate are deformed, damages  
to the inner components can be minimized and the  
apparatus can be down-sized and made lightweight to  
make it conveniently portable. When the containers or  
10 the air bags are made to contain cooling liquid, the  
circuit is encouraged to emit heat in an efficient way.